

RBB10DHRQ

uest a Quote

RBB10DHRQ Information

Code lenser . com	Part Number	RBB10DHRQ	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 20POS 0.050	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RBB10DHRQ Specifications

Manufacturer Part Number RBB IODHRQ Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Package - Stries - Card Type Mon Specified - Dual Edge Gender Female Number of Positions/Bay/Row 10 Number of Positions/Bay/Row 04 Number of Positions 04 Youth of Positions 0.050°t (1.57mm) Number of Rows 2 Pactures 0.050°t (1.27mm) Number of Rows 2 Youth of Edge Straddle Mount Solder Youth Of Stradd			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.050° (1.27mm)FeaturesGoard Edge, Straddle MountNounting TypeBoard Edge, Straddle MountContact FinishSolderContact FinishThicknessI.0ju (0.25µm)Contact FinishThicknessI.0ju (0.25µm)Color-FauresStradle Mount Opening, Unthreaded, 0.078" (1.98mm)ColorStradle Mount Opening, Unthreaded, 0.078" (1.98mm)Color-FinishThicknessStradle Mount Opening, Unthreaded, 0.078" (1.98mm)Color-Fining FeatureStradle Mount Opening, Unthreaded, 0.078" (1.98mm)	Manufacturer Part Number	RBB10DHRQ	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeSolderContact MaterialSolderContact FinishGoldContact FinishGoldContact Finish Thickness10Coltact TypeHarjin BellowsColtact Type-Fange FeatureStadle Mount Opening, Unthreaded, 0.078" (1.98mm)Openating Temperature65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.602" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)FeaturesCard EtxenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIpin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNosphor BronzeContact FinishGoldContact Finish ThicknessGoldContact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Openting Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish ThicknessIujui (0.25µm)Contact Type-Color-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-Stradle Mount Opening, Unthreaded, 0.078" (1.98mm)	Package	-	
GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Depening. (1.98mm)Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.50" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Color - Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColor-Flange FeatureStraddle Mount D.078" (1.98mm)Operating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	10	
Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Color-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Number of Positions	20	
Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact Type-Color-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Color-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Features	Card Extender	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColor-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color-Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-	
	Flange Feature	Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)	
Report errors?	Operating Temperature	-65°C ~ 125°C	
		Report errors?	

RBB10DHRQ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RBB10DHRQ Payment Methods



RBB10DHRQ Shipping Methods



If you have any question about RBB10DHRQ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com