



# **RBB24DYRQ Information**

Heisener.com

Part Number RBB24DYRQ

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 48POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **RBB24DYRO Specifications**

Manufacturer Part Number         RBB24DYRQ           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 125°C	RDD24D1 RQ Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	RBB24DYRQ
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         Black           Flange Feature         Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	24
Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Number of Positions	48
Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, $0.078$ " (1.98mm)Operating Temperature $-65$ °C $\sim 125$ °C	Pitch	0.050" (1.27mm)
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color Black  Flange Feature Straddle Mount Opening, Unthreaded, $0.078''$ ( $1.98mm$ )  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature $-65$ °C ~ $125$ °C	Mounting Type	Board Edge, Straddle Mount
Contact Finish  Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type  Cantilever  Color  Black  Flange Feature  Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)  Operating Temperature  -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, $0.078''$ (1.98mm) Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Straddle Mount Opening, Unthreaded, $0.078$ " (1.98mm)  Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	Straddle Mount Opening, Unthreaded, 0.078" (1.98mm)
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **RBB24DYRQ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RBB24DYRQ Payment Methods**





















## **RBB24DYRQ Shipping Methods**













If you have any question about RBB24DYRQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com