

RBB25DYHR

RBB25DYHR Information

Heisener.com	 RBB25DYHR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 50POS 0.050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RBB25DYHR Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Number of Rows2Pich0.050" (1.27mm)Number of Rows2PichSolder Acta ConnectorsMunting TypeSolder Acta ConnectorsNonting TypeSolder StageredContact FinishGoldContact Finish ThicknessJuin (0.25µm)Contact TypeCantileverContact TypeGual CockContact TypeSolder StageredContact Finish ThicknessGualContact TypeGual CockContact TypeSolder StageredContact TypeSolder StageredContact Finish ThicknessSolder StageredContact TypeSolder StageredContact Finish ThicknessSolder StageredContact Finish ThicknessSolder StageredContact TypeSolder StageredContact Finish ThicknessSolder StageredContact Finish TypeSolder StageredContact Finish TypeSolder Stagere	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness0.061Contact Finish Thickness0.010Contact TypeCantileverContact TypeGaldContact TypeCantileverContact TypeSolder, StaggeredContact TypeCantileverContact TypeGoldContact TypeCantileverContact TypeCantileverFauge Feature-Coperating Temperature-Core State Sta	Manufacturer Part Number	RBB25DYHR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5%° ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact FinishSolder, StaggeredContact Finish ThicknessI0µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-Solor Al25°C-		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialOolder, StaggeredContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeBackFlange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSolder, StaggeredContact MaterialGoldContact FinishGoldContact TypeGoldContact TypeInjui (0.25µm)ColorBlackFange Feature-Operating Temperature-6°C~ 125°C	Series	-
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness Ioµin (0.25µm) Contact Type Cantilever Color Black Flange Feature -<	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	25
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	50
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeIupin (0.25µm)ColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI/µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperatures-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 125°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Features	Board Lock
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

RBB25DYHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RBB25DYHR Payment Methods



RBB25DYHR Shipping Methods



If you have any question about RBB25DYHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com