

RBB50DYHR

RBB50DYHR Information

Heisener.com	 RBB50DYHR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 100POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RBB50DYHR Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions0.062" (1.57mm)Number of Rows2Pich0.050" (1.27mm)Number of Rows2PicturesBoard LockMounting TypeSolder, StaggeredContact FinishGoldContact Finish Thickness0.01Contact Finish Thickness0.02Contact TypeGuileverContact Specifies1.01Contact Finish Thickness0.02Contact Finish Thickness0.02Contact Specifies1.01Contact Finish Thickness0.02Contact Specifies1.01Contact Specifies1.02Contact Specifies0.02Contact Specifies0.	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact FinishSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeGaidContact TypeGaidContact TypeSolder, StaggeredContact TypeGaidContact TypeGaidContact TypeSolder, StaggeredContact TypeGaidContact TypeGaidContact TypeGaidContact TypeSolder, StaggeredContact TypeSolder, StaggeredContact TypeGaidContact TypeGaidContact TypeSolder, StaggeredContact TypeSolder, StaggeredC	Manufacturer Part Number	RBB50DYHR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-50°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact Finish ThicknessSolder, StaggeredContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish ThicknessGoldContact Finish ThicknessInpin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSolder, StaggeredContact MaterialGoldContact FinishGoldContact TypeInpin (0.25µm)Contact TypeBackFlange Feature-Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.50" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness I0µin (0.25µm) Contact Type Cantilever Color Black Flange Feature -<	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	50
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	100
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeI0µin (0.25µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI/uin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperatures-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Features	Board Lock
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

RBB50DYHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RBB50DYHR Payment Methods



RBB50DYHR Shipping Methods



If you have any question about RBB50DYHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com