



# **RBB64DHAR Information**

Heisener.com

Part Number RBB64DHAR

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 128POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RBB64DHAR Specifications**

Manufacturer Part Number         RBB64DHAR           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         64           Number of Positions         128           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Board Lock           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 125°C	RDD04D11/1R Specifications	
Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       64         Number of Positions       128         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       Board Lock         Mounting Type       Through Hole, Right Angle         Termination       Solder, Staggered         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       -         Operating Temperature       -65°C ~ 125°C	Manufacturer Part Number	RBB64DHAR
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         64           Number of Positions         128           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Board Lock           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Type         Hairpin Bellows           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         64           Number of Positions         128           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Board Lock           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         64           Number of Positions         128           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Board Lock           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row64Number of Positions128Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Cotact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Package	-
Gender         Female           Number of Positions/Bay/Row         64           Number of Positions         128           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.050" (1.27mm)           Features         Board Lock           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         Black           Flange Feature         -           Operating Temperature         -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row  128 Card Thickness 0.062" (1.57mm)  Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Operating Temperature 65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions128Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	64
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	128
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)
Termination Solder, Staggered  Contact Material Phosphor Bronze  Contact Finish  Contact Finish Thickness  10μin (0.25μm)  Contact Type Hairpin Bellows  Color Black  Flange Feature  - Operating Temperature  Solder, Staggered  Phosphor Bronze  Gold	Features	Board Lock
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Hairpin Bellows  Color Black  Flange Feature -  Operating Temperature -65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact Type Hairpin Bellows  Color Black  Flange Feature  Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature - Generating Temperature -65°C $\sim$ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **RBB64DHAR Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RBB64DHAR Payment Methods**



















## **RBB64DHAR Shipping Methods**













If you have any question about RBB64DHAR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com