



## **RBB90DYFD Information**

Heisener.com

Part Number RBB90DYFD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 180POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **RBB90DYFD Specifications**

Manufacturer Part Number       RBB90DYFD         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       90         Number of Positions       180         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Surface Mount         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	RDD/0D II D Specifications		
Category Cand Edge Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Surface Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	RBB90DYFD	
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Surface Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Surface Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Surface Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card Type	Package	-	
Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Surface Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-	
Number of Positions       90         Number of Positions       180         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Surface Mount         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions       180         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Surface Mount         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features -  Mounting Type Surface Mount  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	90	
Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Surface Mount         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	180	
Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Surface Mount         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)	
Features  Mounting Type Surface Mount  Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2	
Mounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.050" (1.27mm)	
Termination  Solder  Contact Material  Phosphor Bronze  Contact Finish  Gold  Contact Finish Thickness  10μin (0.25μm)  Contact Type  Cantilever  Color  Black  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-	
Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Surface Mount	
Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder	
Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze	
Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Cantilever	
	Color	Black	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 125°C	
Report errors'		Report errors	s?

#### **RBB90DYFD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RBB90DYFD Payment Methods**



















# **RBB90DYFD Shipping Methods**













If you have any question about RBB90DYFD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com