



RBC17DRTS-S13 Information

Heisener.com

Part Number RBC17DRTS-S13

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 34POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RBC17DRTS-S13 Specifications

Manufacturer Part Number RBC17DRTS-S13 Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C Report errors?	•	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	RBC17DRTS-S13
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature 65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	17
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	34
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Features	Card Extender
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Mounting Type	Board Edge, Straddle Mount
Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

RBC17DRTS-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RBC17DRTS-S13 Payment Methods



















RBC17DRTS-S13 Shipping Methods













If you have any question about RBC17DRTS-S13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com