

## **RBC20DRES-S13**

est a Quote

#### **RBC20DRES-S13 Information**

Heisener.com	Part Number	RBC20DRES-S13	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 40POS 0.100	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RBC20DRES-S13 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions/Bay/Row0062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGord Edge, Straddle MountFeaturesSolder Edge, Straddle MountContact ThinknessSolder Edge, Straddle MountContact Finish ThicknessGoldContact Finish ThicknessIopin (0.52µm)Contact TypeFeaturesContact TypeFeaturesContact TypeFeaturesContact Finish ThicknessIopin (0.52µm)Contact TypeFeaturesContact TypeFeaturesContact TypeFeaturesFange FeatureSied Mount Opening, Unthreaded, 0.125" (3.18mm) Dia			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions/Bay/Row0062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGard Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact MaterialSolder Eyelet(s)Contact Finish Thickness0.04Contact Finish Thickness10µin (0.25µm)Contact TypeFeallelowsContact TypeSolder SellowsContact TypeFeallowsContact TypeSolder SellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	RBC20DRES-S13	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Rumber of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-5°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeFeil BellowsContact TypeGenenContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating TemperatureSide Yac2S°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Series	-	
Number of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 40   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features Card Extender   Mounting Type Board Edge, Straddle Mount   Termination Solder Eyelet(s)   Contact Material Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Type Full Bellows   Color Green   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	20	
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	40	
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)	
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Green	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$	
		Report errors	

#### **RBC20DRES-S13** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RBC20DRES-S13 Payment Methods**



## RDC20DRES-515 Shipping Methods



If you have any question about RBC20DRES-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com