



RBC20HETS Information

Heisener.com

Part Number RBC20HETS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 20POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RBC20HETS Specifications

Manufacturer Part Number RBC20HETS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	RDC2011E15 Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	RBC20HETS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row - Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 1 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows1Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Number of Positions	20
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65° C ~ 125°C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) DiaOperating Temperature -65° C ~ 125° C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

RBC20HETS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RBC20HETS Payment Methods





















RBC20HETS Shipping Methods













If you have any question about RBC20HETS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com