



RBC31DREF Information

Heisener.com

Part Number RBC31DREF

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 62POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RBC31DREF Specifications

Manufacturer Part Number RBC31DREF Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	RDC31DRET Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	RBC31DREF	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Cotact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	31	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	62	
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Features	-	
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature -65 °C ~ 125 °C	Mounting Type	Panel Mount	
Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Termination	Solder Eyelet(s)	
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, $0.116''$ (2.95mm) Dia Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Contact Material	Phosphor Bronze	
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

RBC31DREF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RBC31DREF Payment Methods





















RBC31DREF Shipping Methods













If you have any question about RBC31DREF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com