



RBM28DRYI Information

Heisener.com

Part Number RBM28DRYI

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 56POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RBM28DRYI Specifications

Manufacturer Part Number RBM28DRYI Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Cotact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Manufacturer Part Number	RBM28DRYI
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Package	-
Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Series	-
Number of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Card Type	Non Specified - Dual Edge
Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Flange Feature Top Mount Opening, Threaded Insert, 4-40	Gender	Female
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Number of Positions/Bay/Row	28
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Number of Positions	56
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Card Thickness	0.062" (1.57mm)
Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Threaded Insert, 4-40	Contact Type	Full Bellows
	Color	Green
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
	Operating Temperature	-65°C ~ 125°C
Report errors?		Report errors?

RBM28DRYI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RBM28DRYI Payment Methods



















RBM28DRYI Shipping Methods













If you have any question about RBM28DRYI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com