

RCA24DTMH

uest a Quote

RCA24DTMH Information

Part Number	RCA24DTMH	
Manufacturer	Sullins Connector Solutions	
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
Description	CONN EDGE DUAL FMALE 48POS 0.125	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Description CONN EDGE DUAL FMALE 48POS 0.125 Package - For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RCA24DTMH Specifications

ManufacturerSullins Connector SolutionsCardege ConnectorsCard Edge ConnectorsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions/Bay/Row0602° (1.57mm)Number of Rows0.602° (1.57mm)Number of Rows0.602° (1.57mm)Features-Number of Rows0.125° (3.18mm)Fouting TypeSolderOratot MaterialSolderContact FinishGoldContact FinishGoldContact TypeSolin (0.76µm)Contact TypeGoldContact TypeGolderContact Finish ThicknessGoldContact TypeGoldenseContact TypeGoldenseContact TypeGongenlowsContact Type			
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Card Thickness0.062" (1.57mm)Number of Rows2Pich0.125" (3.18mm)Features-Mounting Type-Contact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeIcop BellowsContact TypeGreenFauge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	RCA24DTMH	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions8Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact TypeLoop BellowsFolorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions/Bay/Row48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessJop BellowsColorGreenFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSujuin (0.76µm)Contact TypeLoop BellowsColorGreenFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact FinishGoldContact FinishGoldContact TypeJouin (0.76µm)Contact TypeLoop BellowsColorGreenFange FeatureTony Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-	
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureeTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-	
Number of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type0.125" (3.18mm)TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeJojin (0.76µm)Contact TypeGorenFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeJujin (0.76µm)Contact TypeGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	24	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	48	
Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.125" (3.18mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder	
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold	
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows	
	Color	Green	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 125°C	
Report errors?		Report errors?	

RCA24DTMH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RCA24DTMH Payment Methods



RCA24DTMH Shipping Methods



If you have any question about RCA24DTMH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com