

# **RCB34DHAS**

uest a Quote

## **RCB34DHAS Information**

Heisener.com	Part Number	RCB34DHAS	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	Ż
	Description	CONN EDGE DUAL FMALE 68POS 0.050	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **RCB34DHAS Specifications**

Manufacturer Part Number RCB34DHAS   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Card Edge Connectors - Edgeboard Connectors Card Edge Connectors - Edgeboard Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 34   Number of Positions/Bay/Row 68   Number of Rows 0.062° (1.57mm)   Number of Rows 2   Pitch 0.050° (1.27mm)   Number of Rows 2   Pitch Solder, Staggered   Youngt Hole, Right Angle Solder, Staggered   Contact Finish Thickness Gold   Contact Finish Thickness Goldy (0.50mm)   Contact Type Biack   Contact Type Biack   Contact Type Solut Orthogement   Contact Type Solut Opening, Unthreaded, 0.125° (3.18mm) Dia   Color Biack	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row34Number of Positions/Bay/Row68Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Nong Hole, Right AngleSolder, StaggeredContact FinishSolder, StaggeredContact FinishGoldContact Finish ThicknessJuin (0.76µm)Contact Finish ThicknessSiden (0.62µm)Contact Finish ThicknesSiden (0.62µ	Manufacturer Part Number	RCB34DHAS	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting Type50/der, StaggeredContact MaterialGoldContact Finish ThicknessGoldContact Finish ThicknessGuldContact Finish ThicknessSiden, StaggeredContact Finish ThicknessSiden (2.5°m)Colar TypeHairpin BellowsColar TypeSiden (2.5°m)Fining FeatureSide Nout Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature-Sice ~ 125°C-	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row34Number of Positions68Card Thickness0.602" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)Features-Mounting Typeof Solder, StaggeredContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row34Number of Positions68Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeHairpin BellowsColorBackFaquereeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature-55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row34Number of Positions68Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialPosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row34Number of Positions68Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessBialkColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row34Number of Positions68Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)Features-Mounting Type-Mounting TypeSolder, StaggeredContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-Solor C 25°C-	Card Type	Non Specified - Dual Edge	
Number of Positions 68   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.050" (1.27mm)   Features -   Mounting Type Through Hole, Right Angle   Termination Solder, Staggered   Contact Material Phosphor Bronze   Contact Finish Gold   Contact Finish Thickness 30µin (0.76µm)   Color Black   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting Type-TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeBiakin GoldColorBiakin GoldFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	34	
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	68	
Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)	
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder, Staggered	
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

### **RCB34DHAS Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RCB34DHAS Payment Methods**





If you have any question about RCB34DHAS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com