

# RCB60DHFD-S578

Quote

## **RCB60DHFD-S578 Information**

Heisener.com	Part Number	RCB60DHFD-S578	
	Manufacturer	Sullins Connector Solutions	Tel North
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN PCI CARDEDGE FEMALE 120POS	- X.F.
	Package	-	
		For the pricing/inventory/lead time, please contact	E12.399
For Reference Only		us Wahaita https://www.haisanan.com	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **RCB60DHFD-S578** Specifications

ManufacturerSullins Connector SolutionsCardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions0.062" (1.57mm)Card Type0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact ThinknessSolderContact FinishGoldContact Finish ThicknessGuid (0.76µm)Contact TypeHairpi BellowsContact TypeBackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia				
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions0.062° (1.57mm)Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.050° (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact TypeGuido (0.6µm)Contact TypeBiackFalage FeatureFush Mount, Top Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	RCB60DHFD-S578		
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)BeaturesBoard GuideMounting TypeSurface MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects		
Series-Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact FinishSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors		
Card TypePCI 3.3V, 5V 32 Bit (Universal)GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact MaterialPolysphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-		
GenderFemaleNumber of Positions/Bay/Row11; 49Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact MaterialPhosphor BronzeContact FinishGoldContact TypeGoldContact TypeBiackFauresBiackForge FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-		
Number of Positions/Bay/Row11; 49Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountContact MaterialPolsphor BronzeContact FinishGoldContact TypeGuju (0.76µm)Contact TypeBiackFauresBiackForge FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	PCI 3.3V, 5V 32 Bit (Universal)		
Number of Positions 120   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.050" (1.27mm)   Features Board Guide   Mounting Type Surface Mount   Termination Solder   Contact Material Gold   Contact Finish Gold   Contact Type Muin (0.76µm)   Color Black   Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female		
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	11; 49		
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	120		
Pitch0.050" (1.27mm)FeaturesBoard GuideMounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)		
FeaturesBoard GuideMounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2		
Mounting TypeSurface MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)		
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Board Guide		
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Surface Mount		
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder		
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze		
Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold		
ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)		
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows		
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black		
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		
Report errors?	Operating Temperature	-65°C ~ 125°C		
			Report errors?	

### **RCB60DHFD-S578** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RCB60DHFD-S578** Payment Methods





If you have any question about RCB60DHFD-S578, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com