

RCB85DHBS

uest a Quote

RCB85DHBS Information

Heisener.com	Part Number	RCB85DHBS	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 170POS .050	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RCB85DHBS Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleSumber of Positions/Bay/Row85Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Features-Contact MaterialSolder, StaggeredContact Finish ThicknessOidContact TypeGoldContact TypeGuin (0.76µm)Contact TypeBiackColorBiackColorSolder, Staggered, 0.125" (3.18mm) DiaColorSolder, Staggered, 0.					
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row85Number of Positions/Bay/Row062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)Features-Features-Contact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeBlackColorBlackFaque Feature-ColorSick Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	RCB85DHBS			
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 85 Number of Positions 170 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Contact Material Solder, Staggered Contact Finish Gold Contact Type Hairpin Bellows Color Black Color Black Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions			
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row85Number of Positions170Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects			
Series-Card TypeNon Specified - Dual EdgeGenderFemaleSumber of Positions/Bay/Row85Number of Positions/Bay/Row170Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µi (0.76µm)Contact TypeHairpin BellowsColorBlackFaque FeaturesSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors			
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row85Number of Positions170Card Thickness0.062" (1.57mm)Card Thickness2Pitch0.500" (1.27mm)Features-Mounting TypeMongher of RossContact MaterialSolder, StaggeredContact FinishGoldContact Finish ThicknessJopin (0.76µm)Contact TypeBackColorBackFeaturesSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-			
GenderFemaleNumber of Positions/Bay/Row85Number of Positions170Card Thickness0.062" (1.57mm)Card Thickness2Pitch0.050" (1.27mm)Features-Features-PreminationSolder, StaggeredContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Series	-			
Number of Positions/Bay/Row85Number of Positions170Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge			
Number of Positions170Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact FinishGoldContact Type30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female			
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	85			
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleFerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	170			
Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleFerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)			
Features-Mounting TypeThrough Hole, Right AngleFerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2			
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)			
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-			
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle			
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder, Staggered			
Contact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze			
Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold			
ColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)			
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows			
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black			
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia			
	Operating Temperature	-65°C ~ 125°C			
Report errors?			Report errors?		

RCB85DHBS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RCB85DHBS Payment Methods





If you have any question about RCB85DHBS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com