

RCB90DYHR

equest a Quote

RCB90DYHR Information

Part Number	RCB90DYHR
Manufacturer	Sullins Connector Solutions
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
Description	CONN EDGE DUAL FMALE 180POS .050
Package	-
	For the pricing/inventory/lead time, please contact
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RCB90DYHR Specifications

ManufacturerSullins Connector SolutionsCardege Connectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeHouge HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeCantileverContact TypeGanileverFange FeatureJackFange FeatureSalexFange FeatureSalexFan	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeGoldContact TypeSolder, StaggeredContact TypeSolder StaggeredContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessSolder, StaggeredColorBlackFlange Feature-Operating Temperature-Soler 2125°CScore 125°C	Manufacturer Part Number	RCB90DYHR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions/Bay/Row180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact Finish ThicknessSolder, StaggeredContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-Operating Temperature-Operating Temperature-Contact Strengt-StrengtStrengtContact Type-ColorStrengtColorStrengtContact Strengt-ColorStrengtColorStrengtContact Strengt-ColorStrengtContact Strengt-Contact Strengt-ColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengtColorStrengt </td <td></td> <td>Card Edge Connectors - Edgeboard Connectors</td>		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggredContact FinishGoldContact TypeGoldContact TypeSoluri (0.76µm)ColorBlackFlange Feature-Operating Temperature-5°C ~ 125°C	Series	-
Number of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact TypeGoldContact TypeSolpin (0.76µm)ColorBlackFlange Feature-Operating Temperature-5°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	90
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	180
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessSoldir, StaguerodContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Features	Board Lock
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

RCB90DYHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RCB90DYHR Payment Methods



RCB90DYHR Shipping Methods



If you have any question about RCB90DYHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com