

# **RCB95DHBS**

#### **RCB95DHBS Information**

Heisener.com	 RCB95DHBS Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 190POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RCB95DHBS Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions/Bay/Row0602" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishGoldContact FinishGoldContact TypeGoldContact TypeBackColorBackFaqueresSide Nout Opening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperature-65°C ~ 125°C	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.500° (1.27mm)Features-Mounting TypeSolder, StaggeredContact MaterialSolder, StaggeredContact Finish Thickness0.0ju (0.76µm)Contact TypeGoldContact TypeBiackColorBiackFaquere FeatureSied Mount Opening, Unthreaded, 0.125° (3.18mm) DiaCoperating Temperature-55°C ~ 125°C	Manufacturer Part Number	RCB95DHBS
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)Mounting Type-Mounting TypeSolder, StaggeredContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaFlange Feature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeOlofer, StaggeredContact MaterialSolder, StaggeredContact Finish ThicknessGoldContact TypeHairpin BellowsContact TypeBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact FinishGoldContact TypeGoldContact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row95Number of Positions190Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolder, StaggeredContact FinishGoldContact TypeGoldContact TypeBiackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 190   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.050" (1.27mm)   Features -   Mounting Type Through Hole, Right Angle   Termination Solder, Staggered   Contact Material Phosphor Bronze   Contact Finish Gold   Contact Type Hairpin Bellows   Color Black   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	95
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	190
Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder, Staggered
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeHairpin BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **RCB95DHBS** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **RCB95DHBS Payment Methods**





If you have any question about RCB95DHBS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com