

RCC55DCAI

RCC55DCAI Information

Heisener.com	 RCC55DCAI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 110POS .100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RCC55DCAI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions0.062" (1.57mm)Card Type0.100" (2.54mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact ThinknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGoldContact TypeGreenFlange Feature- So Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeHairpi BellowsContact TypeGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65% ~ 125°C	Manufacturer Part Number	RCC55DCAI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeGreenFlange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeGreenFlage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange Feature-Operating Temperature-Operating Temperature-Contact Strenge-Contact Strenge-Contact TypeSolderContact Type-ColorGreenColor-Contact Strenge-Contact Strenge-Contact Strenge-Contact Strenge-ColorGreenColor-Color		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeHairpin BellowsColorGreenFlange Feature-Operating Temperature-55°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeGoldContact TypeGoldColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Series	-
Number of Positions/Bay/Row55Number of Positions110Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeJuji (0.76µm)ColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 110 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Mounting Type Solder Contact Material Gold Contact Finish Gold Contact Type Hairpin Bellows Color Green Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	55
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	110
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

RCC55DCAI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about RCC55DCAI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com