

RCM06DCMH-S288

RCM06DCMH-S288 Information

	Part Number	RCM06DCMH-S288	
	Manufacturer	Sullins Connector Solutions	Filling Sol
() Heisener.com	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
A. Contraction	Description	CONN EDGE DUAL FMALE 12POS 0.156	- 神行動
	Package	-	i in the second
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



uote

RCM06DCMH-S288 Specifications

ManufacturerSullins Connector SolutionsCardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesGand Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact FinishOidouContact Finish Thickness0.jui (0.76µm)Contact TypeGaidContact TypeGuju (0.76µm)Contact TypeGip SenzeContact SenseSupin (0.76µm)Contact TypeGip SenzeContact TypeGip SenzeColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	-	
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row0.062° (1.57mm)Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)FeaturesGard Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact FinishOidouContact Finish Thickness0.0id (0.76µm)Contact TypeGoldContact TypeGipin BellowsContact TypeGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	RCM06DCMH-S288
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialVire WrapContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialOidContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange Feature0.0125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialYie WrapContact FinishGoldContact Type30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Wire Wrap Contact Material Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	6
Number of Rows2Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	12
Pitch0.156" (3.96mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Wire Wrap
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeHairpin BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report error

RCM06DCMH-S288 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RCM06DCMH-S288 Payment Methods





If you have any question about RCM06DCMH-S288, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com