



RD0504T-TL-H Information



For Reference Only

Part Number RD0504T-TL-H
Manufacturer ON Semiconductor

Category Discrete Semiconductor Products
Diodes - Rectifiers - Single

DescriptionDIODE GEN PURP 400V 5A TPFA**Package**TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RD0504T-TL-H Specifications

Manufacturer Part NumberRD0504T-TL-HManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.5V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)		
Category Discrete Semiconductor Products Diodes - Rectifiers - Single TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) Sons Current - Reverse Leakage @ Vr 20µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction Diodes - Rectifiers - Single TO-252-3, DPak (2 Leads + Tab), SC-63 TP-FA Operating Temperature - Junction	Manufacturer Part Number	RD0504T-TL-H
Diodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.5V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)	Manufacturer	ON Semiconductor
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.5V @ 5A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 20µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package Operating Temperature - Junction 150°C (Max)	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.5V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.5V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package Operating Temperature - Junction 400V 5A 1.5V @ 5A 1.5V @ 5A 50ns Current - Surface Mount To-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.5V @ 5A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 20µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package Operating Temperature - Junction 5A 1.5V @ 5A 1.5V @ 5A Fast Recovery =< 500ns, > 200mA (Io) Suns Fast Recovery =< 500ns, > 200mA (Io) Fast Recovery =< 50ns Fast Recovery =< 50ns Fast Recovery =< 50ns Fast Recovery =< 500ns Fast Recovery =	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 20μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Voltage - DC Reverse (Vr) (Max)	400V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)	Current - Average Rectified (Io)	5A
Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr20μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTP-FAOperating Temperature - Junction150°C (Max)	Voltage - Forward (Vf) (Max) @ If	1.5V @ 5A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Reverse Recovery Time (trr)	50ns
Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Current - Reverse Leakage @ Vr	20μA @ 400V
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Capacitance @ Vr, F	-
Supplier Device Package TP-FA Operating Temperature - Junction 150°C (Max)	Mounting Type	Surface Mount
Operating Temperature - Junction 150°C (Max)	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
	Supplier Device Package	TP-FA
Report errors?	Operating Temperature - Junction	150°C (Max)
The state of the s		Report errors?

RD0504T-TL-H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RD0504T-TL-H Payment Methods



















RD0504T-TL-H Shipping Methods













If you have any question about RD0504T-TL-H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com