



### RER40F38R3MC02 Information

Heisener.com

Part Number RER40F38R3MC02

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 38.3 OHM 1% 5W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER40F38R3MC02 Specifications**

Manufacturer Part NumberRER40F38R3MC02ManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance38.3 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		
Category         Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER40           Resistance         38.3 Ohms           Tolerance         ±1%           Power (Watts)         5W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant, Non-Inductive           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.600" L x 0.646" W (15.24mm x 16.41mm)           Height - Seated (Max)         0.335" (8.51mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         M (1%)	Manufacturer Part Number	RER40F38R3MC02
Chassis Mount Resistors  Package Axial, Box Military, MIL-PRF-39009, RER40  Resistance 38.3 Ohms  Tolerance ±1%  Power (Watts) 5W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max) 0.335" (8.51mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M(1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance38.3 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER40Resistance38.3 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		Chassis Mount Resistors
Resistance38.3 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance ±1%  Power (Watts) 5W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max) 0.335" (8.51mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Series	Military, MIL-PRF-39009, RER40
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max)  0.335" (8.51mm)  Lead Style  Package / Case  Axial, Box  Failure Rate  M (1%)	Resistance	38.3 Ohms
CompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max) 0.335" (8.51mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Power (Watts)	5W
Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max)  0.335" (8.51mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  M (1%)	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max)  0.335" (8.51mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  M (1%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature  Flanges  Size / Dimension  0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max)  1.24 Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  M (1%)	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm)  Height - Seated (Max) 0.335" (8.51mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  M (1%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	0.600" L x 0.646" W (15.24mm x 16.41mm)
Package / Case Axial, Box Failure Rate M (1%)	Height - Seated (Max)	0.335" (8.51mm)
Failure Rate M (1%)	Lead Style	Solder Lugs
· ·	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
Report errors:		Report errors?

#### RER40F38R3MC02 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RER40F38R3MC02 Payment Methods**



















## **RER40F38R3MC02 Shipping Methods**













If you have any question about RER40F38R3MC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com