

RER40F49R9MC02

RER40F49R9MC02 Information

Heisener.com

Part Number RER40F49R9MC02

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 49.9 OHM 1% 5W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER40F49R9MC02 Specifications

Manufacturer Part Number RER40F49R9MC02 Manufacturer Vishay Dale Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER40 Resistance 49.9 Ohms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)		
Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER40 Resistance 49.9 Ohms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Manufacturer Part Number	RER40F49R9MC02
Chassis Mount Resistors Package Axial, Box Military, MIL-PRF-39009, RER40 Resistance 49.9 Ohms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M(1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance49.9 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Heigh - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER40Resistance49.9 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		Chassis Mount Resistors
Resistance49.9 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20pm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Series	Military, MIL-PRF-39009, RER40
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Package / Case Axial, Box Failure Rate M (1%)	Resistance	49.9 Ohms
CompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Power (Watts)	5W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 1.24	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate M (1%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	0.600" L x 0.646" W (15.24mm x 16.41mm)
Package / Case Axial, Box Failure Rate M (1%)	Height - Seated (Max)	0.335" (8.51mm)
Failure Rate M (1%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
		Report errors?

RER40F49R9MC02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER40F49R9MC02 Payment Methods





















RER40F49R9MC02 Shipping Methods













If you have any question about RER40F49R9MC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com