

RER40F8R06RCSL

RER40F8R06RCSL Information

Heisener.com

Part Number RER40F8R06RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 8.06 OHM 1% 5W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER40F8R06RCSL Specifications

Manufacturer Part NumberRER40F8R06RCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance8.06 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box		
CategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance8.06 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Manufacturer Part Number	RER40F8R06RCSL
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER40 Resistance 8.06 Ohms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance8.06 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER40Resistance8.06 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box		Chassis Mount Resistors
Resistance8.06 OhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Package	Axial, Box
Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Series	Military, MIL-PRF-39009, RER40
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Package / Case Axial, Box	Resistance	8.06 Ohms
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Tolerance	±1%
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Power (Watts)	5W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Operating Temperature	-55°C ~ 250°C
Mounting Feature Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case 0.335" (8.51mm) Solder Lugs Axial, Box	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, Box	Size / Dimension	0.600" L x 0.646" W (15.24mm x 16.41mm)
Package / Case Axial, Box	Height - Seated (Max)	0.335" (8.51mm)
	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Failure Rate R (0.01%)	Failure Rate	R (0.01%)
Report errors?		Report errors?

RER40F8R06RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER40F8R06RCSL Payment Methods





















RER40F8R06RCSL Shipping Methods













If you have any question about RER40F8R06RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com