

RER45F1951RCSL

RER45F1951RCSL Information

Heisener.com

Part Number RER45F1951RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1.95K OHM 1% 10W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER45F1951RCSL Specifications

Manufacturer Part Number RER45F1951RCSL Manufacturer Vishay Dale Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 1.95 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm)		
Category Resistors Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 1.95 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension Resistors Military, Moisture Resistant, Non-Inductive O.750" L x 0.800" W (19.05mm x 20.32mm)	Manufacturer Part Number	RER45F1951RCSL
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 1.95 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension Oracle Axial, Box Military, MIL-PRF-39009, RER45 Military, Common Size / 250°C Features Aluminum Non-Inductive Flanges Size / Dimension O.750" L x 0.800" W (19.05mm x 20.32mm)	Manufacturer	Vishay Dale
Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 1.95 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER45Resistance1.95 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)		Chassis Mount Resistors
Resistance 1.95 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Package	Axial, Box
Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Series	Military, MIL-PRF-39009, RER45
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10W Wirewound ### ### ### ### #### ###############	Resistance	1.95 kOhms
CompositionWirewoundTemperature Coefficient $\pm 20 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 250^{\circ}C$ FeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}L \times 0.800^{\circ}W (19.05 mm \times 20.32 mm)$	Tolerance	±1%
Temperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension $0.750^{\circ}\text{L} \times 0.800^{\circ}\text{W} (19.05 \text{mm} \times 20.32 \text{mm})$	Power (Watts)	10W
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}\text{L x } 0.800^{\circ}\text{W } (19.05\text{mm x } 20.32\text{mm})$	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Coating, Housing Type	Aluminum
	Mounting Feature	Flanges
Height - Seated (Max) 0.405" (10.29mm)	Size / Dimension	0.750" L x 0.800" W (19.05mm x 20.32mm)
	Height - Seated (Max)	0.405" (10.29mm)
Lead Style Solder Lugs	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate R (0.01%)	Failure Rate	R (0.01%)
Report errors?		Report errors?

RER45F1951RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER45F1951RCSL Payment Methods



















RER45F1951RCSL Shipping Methods













If you have any question about RER45F1951RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com