

RER45F2R26RCSL

RER45F2R26RCSL Information

Heisener.com

Part Number RER45F2R26RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 2.26 OHM 1% 10W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER45F2R26RCSL Specifications

Manufacturer Part NumberRER45F2R26RCSLManufacturerVishay DaleCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER45Resistance2.26 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminum
Category Resistors Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 2.26 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 2.26 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive
Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 2.26 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive
SeriesMilitary, MIL-PRF-39009, RER45Resistance 2.26 Ohms Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
Resistance 2.26 Ohms Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
$\begin{array}{lll} \begin{tabular}{lll} Tolerance & $\pm 1\%$ \\ Power (Watts) & 10W \\ Composition & Wirewound \\ \hline Temperature Coefficient & $\pm 50 \mathrm{ppm/^{\circ}C}$ \\ Operating Temperature & $-55^{\circ}\mathrm{C} \sim 250^{\circ}\mathrm{C}$ \\ \hline Features & Military, Moisture Resistant, Non-Inductive \\ \hline \end{array}$
Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
$\begin{tabular}{lll} Composition & Wirewound \\ Temperature Coefficient & \pm 50 ppm/^{\circ}C \\ Operating Temperature & -55^{\circ}C \sim 250^{\circ}C \\ Features & Military, Moisture Resistant, Non-Inductive \\ \end{tabular}$
Temperature Coefficient $\pm 50 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive
Features Military, Moisture Resistant, Non-Inductive
Coating, Housing Type Aluminum
Mounting Feature Flanges
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)
Height - Seated (Max) 0.405" (10.29mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate R (0.01%)
Report errors

RER45F2R26RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER45F2R26RCSL Payment Methods



















RER45F2R26RCSL Shipping Methods













If you have any question about RER45F2R26RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com