

# RER45F6R81RC02

### RER45F6R81RC02 Information

Heisener.com

Part Number RER45F6R81RC02

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 6.81 OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER45F6R81RC02 Specifications**

Manufacturer         RER45F6R81RC02           Manufacturer         Vishay Dale           Category         Resistors           Chassis Mount Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER45           Resistance         6.81 Ohms           Tolerance         ±1%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±50ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant, Non-Inductive           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.750" L x 0.800" W (19.05mm x 20.32mm)           Height - Seated (Max)         0.405" (10.29mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         R (0.01%)		
Category         Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER45           Resistance         6.81 Ohms           Tolerance         ±1%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±50ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant, Non-Inductive           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.750" L x 0.800" W (19.05mm x 20.32mm)           Height - Seated (Max)         0.405" (10.29mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box	Manufacturer Part Number	RER45F6R81RC02
Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER45  Resistance 6.81 Ohms  Tolerance ±1%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER45Resistance6.81 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER45Resistance6.81 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, Box		Chassis Mount Resistors
Resistance 6.81 Ohms  Tolerance ±1%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Package	Axial, Box
Tolerance ±1%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Series	Military, MIL-PRF-39009, RER45
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±50ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box	Resistance	6.81 Ohms
Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Tolerance	±1%
Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Power (Watts)	10W
Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max)  0.405" (10.29mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Temperature Coefficient	±50ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max)  0.405" (10.29mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)  Height - Seated (Max) 0.405" (10.29mm)  Lead Style Solder Lugs  Package / Case Axial, Box	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  0.405" (10.29mm)  Solder Lugs  Axial, Box	Mounting Feature	Flanges
Lead Style Solder Lugs Package / Case Axial, Box	Size / Dimension	0.750" L x 0.800" W (19.05mm x 20.32mm)
Package / Case Axial, Box	Height - Seated (Max)	0.405" (10.29mm)
-	Lead Style	Solder Lugs
Failure Rate R (0.01%)	Package / Case	Axial, Box
	Failure Rate	R (0.01%)
Report errors?		Report errors?

#### RER45F6R81RC02 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### RER45F6R81RC02 Payment Methods



















## **RER45F6R81RC02 Shipping Methods**













If you have any question about RER45F6R81RC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com