



RER45F7680RC02 Information

Heisener.com

Part Number RER45F7680RC02

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 768 OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER45F7680RC02 Specifications

Manufacturer Part NumberRER45F7680RC02ManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER45Resistance768 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, Box		
CategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER45Resistance768 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder Lugs	Manufacturer Part Number	RER45F7680RC02
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER45 Resistance 768 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER45Resistance768 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder Lugs	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER45Resistance768 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder Lugs		Chassis Mount Resistors
Resistance 768 Ohms Tolerance $\pm 1\%$ Power (Watts) 10W CompositionWirewoundTemperature Coefficient $\pm 20\text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}\text{L x } 0.800^{\circ}\text{W } (19.05\text{mm x } 20.32\text{mm})$ Height - Seated (Max) $0.405^{\circ} (10.29\text{mm})$ Lead StyleSolder Lugs	Package	Axial, Box
Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Series	Military, MIL-PRF-39009, RER45
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Resistance	768 Ohms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Tolerance	±1%
Temperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension $0.750^{\circ}\text{L x } 0.800^{\circ}\text{W } (19.05 \text{mm x } 20.32 \text{mm})$ Height - Seated (Max) $0.405^{\circ}\text{(10.29 mm)}$ Lead Style Solder Lugs	Power (Watts)	10W
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}\text{L} \times 0.800^{\circ}\text{W} (19.05\text{mm} \times 20.32\text{mm})$ Height - Seated (Max) $0.405^{\circ}\text{(10.29mm)}$ Lead StyleSolder Lugs	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style 0.405" (10.29mm) Solder Lugs	Mounting Feature	Flanges
Lead Style Solder Lugs	Size / Dimension	0.750" L x 0.800" W (19.05mm x 20.32mm)
	Height - Seated (Max)	0.405" (10.29mm)
Package / Case Axial, Box	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Failure Rate R (0.01%)	Failure Rate	R (0.01%)
Report errors?		Report errors?

RER45F7680RC02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER45F7680RC02 Payment Methods



















RER45F7680RC02 Shipping Methods













If you have any question about RER45F7680RC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com