

# RER50F2R87RCSL

### **RER50F2R87RCSL Information**

Heisener.com

Part Number RER50F2R87RCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 2.87 OHM 1% 20W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER50F2R87RCSL Specifications**

Manufacturer Part NumberRER50F2R87RCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance2.87 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-Inductive
Category  Resistors  Chassis Mount Resistors  Package Axial, Box Series Military, MIL-PRF-39009, RER50  Resistance 2.87 Ohms  Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C
Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER50  Resistance 2.87 Ohms  Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance2.87 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°C
SeriesMilitary, MIL-PRF-39009, RER50Resistance $2.87 \text{ Ohms}$ Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Resistance $2.87 \text{ Ohms}$ Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 50 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 250^{\circ}C$
Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Temperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Features Military, Moisture Resistant, Non-Inductive
,
Coating, Housing Type Aluminum
Mounting Feature Flanges
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)
Height - Seated (Max) 0.561" (14.25mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate R (0.01%)
Report errors?

#### **RER50F2R87RCSL Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RER50F2R87RCSL Payment Methods**



















# **RER50F2R87RCSL Shipping Methods**













If you have any question about RER50F2R87RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com