

RER50F36R5MC02

RER50F36R5MC02 Information

Heisener.com

Part Number RER50F36R5MC02

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 36.5 OHM 1% 20W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER50F36R5MC02 Specifications

Manufacturer Part NumberRER50F36R5MC02ManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance36.5 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		
CategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance36.5 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Manufacturer Part Number	RER50F36R5MC02
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER50 Resistance 36.5 Ohms Tolerance ±1% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance36.5 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER50Resistance36.5 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		Chassis Mount Resistors
Resistance36.5 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Series	Military, MIL-PRF-39009, RER50
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Resistance	36.5 Ohms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Power (Watts)	20W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate M (1%)	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate 0.561" (14.25mm) Solder Lugs Axial, Box	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	1.062" L x 1.080" W (26.97mm x 27.43mm)
Package / Case Axial, Box Failure Rate M (1%)	Height - Seated (Max)	0.561" (14.25mm)
Failure Rate M (1%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
		Report errors?

RER50F36R5MC02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER50F36R5MC02 Payment Methods



















RER50F36R5MC02 Shipping Methods













If you have any question about RER50F36R5MC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com