

# RER55F9R09RCSL

# **RER55F9R09RCSL Information**

Part Number RER55F9R09RCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 9.09 OHM 1% 30W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER55F9R09RCSL Specifications**

| Manufacturer Part Number  Manufacturer  Vishay Dale  Resistors  Chassis Mount Resistors  Package  Axial, Box  Series  Military, MIL-PRF-39009, RER55  Resistance  9.09 Ohms  Tolerance  ±1%  Power (Watts)  Composition  Wirewound  Temperature Coefficient  50ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Mounting Feature  Flanges |
|--|
| Category  Resistors  Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER55  Resistance 9.09 Ohms  Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges                                       |
| Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER55  Resistance 9.09 Ohms  Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  |
| PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER55Resistance9.09 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlanges  |
| SeriesMilitary, MIL-PRF-39009, RER55Resistance9.09 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlanges   |
| Resistance 9.09 Ohms  Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  |
| Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  |
| Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±50ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges   |
| Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges  |
| Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive  Coating, Housing Type Aluminum  Mounting Feature Flanges   |
| Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  |
| Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges   |
| Coating, Housing Type Aluminum  Mounting Feature Flanges   |
| Mounting Feature Flanges   |
|  |
| 4.00007 4.4400777 (40.00 0.00 0.00 0.00 0.00 0.00 0.00 0.  |
| Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)   |
| Height - Seated (Max) 0.625" (15.87mm)   |
| Lead Style Solder Lugs   |
| Package / Case Axial, Box  |
| Failure Rate R (0.01%)   |
| Report errors 2  |

### **RER55F9R09RCSL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RER55F9R09RCSL Payment Methods**





















### **RER55F9R09RCSL Shipping Methods**













If you have any question about RER55F9R09RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com