

RER60FR200MC02

RER60FR200MC02 Information

Heisener.com	Part Number Manufacturer Category Description Package	RER60FR200MC02 Vishay Dale Resistors Chassis Mount Resistors RES CHAS MNT 0.2 OHM 1% 5W Axial, Box For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RER60FR200MC02 Specifications

ManufacturerVishay DaleCategoryResistorsChassis Mount ResistorsPackageAxial, BoxPackageMilitary, MIL-PRF-39009, RER60Resistance200 mOhmsTolerance±1%Power (Watts)SWCompositionWirewoundToleparture Coefficient±100ppm°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeFlangesSize / Dimension600° L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseXial, Box		
CategoryResistorsPackageAxial, BoxPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER60Resistance200 mOhmsTolerance±1%Power (Watts)SWCompositionWirewoundTomperature Coefficient±100pm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumSize / Dimension0.600° L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFalure RateMilitary, Mitare CoefficientYende WattsSolder LugsSize / DimensionSolder LugsPackage / CaseMila BoxFalure RateMilitary, Moister ResisterFalure RateSolder LugsPackage / CaseMilitary, Mitare MarceFalure RateMilitary, Mitare ResisterFalure RateMilitary, Mitare Resister	Manufacturer Part Number	RER60FR200MC02
Chassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER60Resistance200 mOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±100ppm°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting Feature51000° L x 0.646° W (15.24mm x 16.41mm)Height - Seated (Max)0.335° (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER60Resistance200 mOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting Feature0.600° L x 0.646° W (15.24mm x 16.41mm)Kied Max)0.335° (8.51mm)Lead StyleSolder LugsPackage / CaseMili BoxFailure RateMili Box	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER60Resistance200 mOhmsTolerance±1%Power (Wats)5WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFalure RateMiltary		Chassis Mount Resistors
Resistance200 mOhmsTolerance±1%Power (Wats)5WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting Feature.660° L x 0.646° W (15.24mm x 16.41mm)Size / Dimension0.335" (8.51mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance±1%Power (Watts)5WCompositionWirewoundComposition±100pm/°COperating Temperature±00pm/°CFeaturesMiltary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600° L x 0.646° W (15.24mm x 16.41mm)Height - Seated (Max)Solder LugsLead StyleSolder LugsPackage / CaseMita)Failure RateMita)	Series	Military, MIL-PRF-39009, RER60
Power (Watts)5WPower (Watts)5WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Resistance	200 mOhms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Tolerance	$\pm 1\%$
Temperature Coefficient±100pm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxKiller RateM (1%)	Power (Watts)	5W
Operating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Composition	Wirewound
FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Temperature Coefficient	±100ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Operating Temperature	-55°C ~ 250°C
Mounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Features	Military, Moisture Resistant
Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	0.600" L x 0.646" W (15.24mm x 16.41mm)
Package / CaseAxial, BoxFailure RateM (1%)	Height - Seated (Max)	0.335" (8.51mm)
Failure RateM (1%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
		Report errors?

RER60FR200MC02 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RER60FR200MC02 Payment Methods





If you have any question about RER60FR200MC02, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com