

RER65F3R48RCSL

RER65F3R48RCSL Information

Heisener.com

Part Number RER65F3R48RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 3.48 OHM 1% 10W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER65F3R48RCSL Specifications

Manufacturer Part NumberRER65F3R48RCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER65Resistance3.48 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		
Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER65 Resistance 3.48 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Manufacturer Part Number	RER65F3R48RCSL
Package Axial, Box Series Military, MIL-PRF-39009, RER65 Resistance 3.48 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER65Resistance3.48 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Heigh - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER65Resistance3.48 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		Chassis Mount Resistors
Resistance3.48 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate Resistant	Series	Military, MIL-PRF-39009, RER65
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Resistance	3.48 Ohms
CompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.405" (10.29mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Tolerance	±1%
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Power (Watts)	10W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Composition	Wirewound
Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Features	Military, Moisture Resistant
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm) Height - Seated (Max) 0.405" (10.29mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Size / Dimension	0.750" L x 0.800" W (19.05mm x 20.32mm)
Package / Case Axial, Box Failure Rate R (0.01%)	Height - Seated (Max)	0.405" (10.29mm)
Failure Rate R (0.01%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	R (0.01%)
Topot direct		Report errors?

RER65F3R48RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER65F3R48RCSL Payment Methods



















RER65F3R48RCSL Shipping Methods













If you have any question about RER65F3R48RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com