

RER65F4700RCSL

RER65F4700RCSL Information

Heisener.com

Part Number RER65F4700RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 470 OHM 1% 10W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER65F4700RCSL Specifications

Manufacturer Part NumberRER65F4700RCSLManufacturerVishay DaleCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER65Resistance470 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlanges
CategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER65Resistance470 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER65 Resistance 470 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER65Resistance470 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
Series Military, MIL-PRF-39009, RER65 Resistance 470 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum
Resistance 470 Ohms Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20\text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 250^{\circ}C$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 250 ^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
CompositionWirewoundTemperature Coefficient $\pm 20 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 250^{\circ}\mathrm{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminum
Temperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant Coating, Housing Type Aluminum
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum
Features Military, Moisture Resistant Coating, Housing Type Aluminum
Coating, Housing Type Aluminum
5, 1 m 6, 1 m 6 VI
Mounting Feature Flanges
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)
Height - Seated (Max) 0.405" (10.29mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate R (0.01%)
Report errors?

RER65F4700RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER65F4700RCSL Payment Methods



















RER65F4700RCSL Shipping Methods













If you have any question about RER65F4700RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com