

# RER70F1001MCSL

## **RER70F1001MCSL Information**

Heisener.com

Part Number RER70F1001MCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 1K OHM 1% 20W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER70F1001MCSL Specifications**

Manufacturer Part NumberRER70F1001MCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER70Resistance1 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		
Category         Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER70           Resistance         1 kOhms           Tolerance         ±1%           Power (Watts)         20W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         1.062" L x 1.080" W (26.97mm x 27.43mm)           Height - Seated (Max)         0.561" (14.25mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         M (1%)	Manufacturer Part Number	RER70F1001MCSL
Chassis Mount Resistors  Package Axial, Box Military, MIL-PRF-39009, RER70  Resistance 1 kOhms  Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M(1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER70Resistance1 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER70Resistance1 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		Chassis Mount Resistors
Resistance1 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Series	Military, MIL-PRF-39009, RER70
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  M (1%)	Resistance	1 kOhms
CompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Power (Watts)	20W
Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max)  0.561" (14.25mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  M (1%)	Composition	Wirewound
Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature  Flanges  Size / Dimension  1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  M (1%)	Features	Military, Moisture Resistant
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  M (1%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	1.062" L x 1.080" W (26.97mm x 27.43mm)
Package / Case Axial, Box Failure Rate M (1%)	Height - Seated (Max)	0.561" (14.25mm)
Failure Rate M (1%)	Lead Style	Solder Lugs
· ·	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
E .		Report errors?

#### **RER70F1001MCSL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RER70F1001MCSL Payment Methods**



















## **RER70F1001MCSL Shipping Methods**













If you have any question about RER70F1001MCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com