

# RER70F4121RCSL

## **RER70F4121RCSL Information**

Heisener.com

Part Number RER70F4121RCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 4.12K OHM 1% 20W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RER70F4121RCSL Specifications**

Manufacturer Part NumberRER70F4121RCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER70Resistance4.12 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)Lead StyleSolder Lugs		
CategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER70Resistance4.12 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)	Manufacturer Part Number	RER70F4121RCSL
Chassis Mount Resistors  Axial, Box  Series Military, MIL-PRF-39009, RER70  Resistance 4.12 kOhms  Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER70Resistance4.12 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER70Resistance4.12 kOhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.561" (14.25mm)		Chassis Mount Resistors
Resistance $4.12 \text{ kOhms}$ Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 20\text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062^{\circ}\text{L} \times 1.080^{\circ}\text{W} (26.97\text{mm} \times 27.43\text{mm})$ Height - Seated (Max) $0.561^{\circ}\text{(14.25\text{mm})}$	Package	Axial, Box
Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)	Series	Military, MIL-PRF-39009, RER70
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max)  0.561" (14.25mm)	Resistance	4.12 kOhms
CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062^{\circ}\text{L} \times 1.080^{\circ}\text{W} (26.97 \text{mm} \times 27.43 \text{mm})$ Height - Seated (Max) $0.561^{\circ}$ (14.25 mm)	Tolerance	$\pm 1\%$
Temperature Coefficient $\pm 20$ ppm/°C  Operating Temperature $-55$ °C $\sim 250$ °C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension $1.062$ " L x $1.080$ " W $(26.97$ mm x $27.43$ mm)  Height - Seated (Max) $0.561$ " $(14.25$ mm)	Power (Watts)	20W
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062^{\circ}\text{L x } 1.080^{\circ}\text{W } (26.97\text{mm x } 27.43\text{mm})$ Height - Seated (Max) $0.561^{\circ}$ (14.25mm)	Composition	Wirewound
Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)  Height - Seated (Max) 0.561" (14.25mm)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.561" (14.25mm)	Features	Military, Moisture Resistant
Size / Dimension       1.062" L x 1.080" W (26.97mm x 27.43mm)         Height - Seated (Max)       0.561" (14.25mm)	Coating, Housing Type	Aluminum
Height - Seated (Max) 0.561" (14.25mm)	Mounting Feature	Flanges
	Size / Dimension	1.062" L x 1.080" W (26.97mm x 27.43mm)
Lead Style Solder Lugs	Height - Seated (Max)	0.561" (14.25mm)
·	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate R (0.01%)	Failure Rate	R (0.01%)
Report errors?		Report errors?

#### **RER70F4121RCSL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RER70F4121RCSL Payment Methods**





















## **RER70F4121RCSL Shipping Methods**













If you have any question about RER70F4121RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com