

RER75F1240RCSL

RER75F1240RCSL Information

Heisener.com

Part Number RER75F1240RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 124 OHM 1% 30W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER75F1240RCSL Specifications

Manufacturer Part Number RER75F1240RCSL Manufacturer Vishay Dale Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 124 Ohms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)		
Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 124 Ohms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Manufacturer Part Number	RER75F1240RCSL
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 124 Ohms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate (R0.01%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance124 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER75Resistance124 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		Chassis Mount Resistors
Resistance124 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Series	Military, MIL-PRF-39009, RER75
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Resistance	124 Ohms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Tolerance	$\pm 1\%$
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Power (Watts)	30W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Composition	Wirewound
Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate Flanges R (0.01%)	Features	Military, Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
Package / Case Axial, Box Failure Rate R (0.01%)	Height - Seated (Max)	0.625" (15.87mm)
Failure Rate R (0.01%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	R (0.01%)
		Report errors?

RER75F1240RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER75F1240RCSL Payment Methods





















RER75F1240RCSL Shipping Methods













If you have any question about RER75F1240RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com