



## RER75F3741RC02 Information

Heisener.com

Part Number RER75F3741RC02

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 3.74K OHM 1% 30W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number         RER75F3741RC02           Manufacturer         Vishay Dale           Category         Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER75           Resistance         3.74 kOhms           Tolerance         ±1%           Power (Watts)         30W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         1.968" L x 1.140" W (49.99mm x 28.96mm)           Height - Seated (Max)         0.625" (15.87mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         R (0.01%)		
Category         Resistors           Package         Axial, Box           Series         Military, MIL-PRF-39009, RER75           Resistance         3.74 kOhms           Tolerance         ±1%           Power (Watts)         30W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 250°C           Features         Military, Moisture Resistant           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         1.968" L x 1.140" W (49.99mm x 28.96mm)           Height - Seated (Max)         0.625" (15.87mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         R (0.01%)	Manufacturer Part Number	RER75F3741RC02
Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER75  Resistance 3.74 kOhms  Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate (R0.01%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance3.74 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER75Resistance3.74 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		Chassis Mount Resistors
Resistance3.74 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Package	Axial, Box
Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate R (0.01%)	Series	Military, MIL-PRF-39009, RER75
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  R (0.01%)	Resistance	3.74 kOhms
Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate R (0.01%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate R (0.01%)	Power (Watts)	30W
Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max)  0.625" (15.87mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  R (0.01%)	Composition	Wirewound
Features Military, Moisture Resistant  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate R (0.01%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max)  0.625" (15.87mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  R (0.01%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature  Size / Dimension  1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  Figure Rate  Flanges  1.968" L x 1.140" W (49.99mm x 28.96mm)  Solder Lugs  Axial, Box  R (0.01%)	Features	Military, Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)  Height - Seated (Max) 0.625" (15.87mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate R (0.01%)	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  0.625" (15.87mm)  Solder Lugs  Axial, Box  R (0.01%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
Package / Case Axial, Box Failure Rate R (0.01%)	Height - Seated (Max)	0.625" (15.87mm)
Failure Rate R (0.01%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	R (0.01%)
		Report errors?

## RER75F3741RC02 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **RER75F3741RC02 Payment Methods**



















## RER75F3741RC02 Shipping Methods













If you have any question about RER75F3741RC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com