



RER75F59R0RC02 Information

Part Number RER75F59R0RC02

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 59 OHM 1% 30W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER75F59R0RC02 Specifications

Manufacturer Part NumberRER75F59R0RC02ManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance59 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder Lugs		
CategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance59 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder Lugs	Manufacturer Part Number	RER75F59R0RC02
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 59 Ohms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance59 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder Lugs	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER75Resistance59 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder Lugs		Chassis Mount Resistors
Resistance59 OhmsTolerance $\pm 1\%$ Power (Watts) $30W$ CompositionWirewoundTemperature Coefficient $\pm 20 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 250^{\circ}\mathrm{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.968^{\circ}\mathrm{L} \times 1.140^{\circ}\mathrm{W} (49.99 \mathrm{mm} \times 28.96 \mathrm{mm})$ Height - Seated (Max) $0.625^{\circ}\mathrm{(15.87 mm)}$ Lead StyleSolder Lugs	Package	Axial, Box
Tolerance $\pm 1\%$ Power (Watts) 30W Composition Wirewound Temperature Coefficient ± 20 ppm/°C Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Series	Military, MIL-PRF-39009, RER75
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Resistance	59 Ohms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Tolerance	±1%
Temperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension $1.968'' \text{L x } 1.140'' \text{W } (49.99 \text{mm x } 28.96 \text{mm})$ Height - Seated (Max) $0.625'' (15.87 \text{mm})$ Lead Style Solder Lugs	Power (Watts)	30W
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.968^{\circ}\text{L} \times 1.140^{\circ}\text{W} (49.99\text{mm} \times 28.96\text{mm})$ Height - Seated (Max) $0.625^{\circ}\text{(}15.87\text{mm})$ Lead StyleSolder Lugs	Composition	Wirewound
Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Operating Temperature	-55°C ~ 250°C
Mounting Feature Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Features	Military, Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style 0.625" (15.87mm) Solder Lugs	Mounting Feature	Flanges
Lead Style Solder Lugs	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
	Height - Seated (Max)	0.625" (15.87mm)
Packaga / Casa Avial Roy	Lead Style	Solder Lugs
1 ackage / Case Axiai, Dox	Package / Case	Axial, Box
Failure Rate R (0.01%)	Failure Rate	R (0.01%)
Report errors?		Report errors?

RER75F59R0RC02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER75F59R0RC02 Payment Methods





















RER75F59R0RC02 Shipping Methods













If you have any question about RER75F59R0RC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com