



RER75F7871RC02 Information

Heisener.com

Part Number RER75F7871RC02

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 7.87K OHM 1% 30W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER75F7871RC02 Specifications

Manufacturer Part NumberRER75F7871RC02ManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance7.87 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		
Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 7.87 kOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Manufacturer Part Number	RER75F7871RC02
Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 7.87 kOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate (R0.01%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance7.87 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER75Resistance7.87 kOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)		Chassis Mount Resistors
Resistance 7.87 kOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Series	Military, MIL-PRF-39009, RER75
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Resistance	7.87 kOhms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Power (Watts)	30W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Composition	Wirewound
Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%)	Features	Military, Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.625" (15.87mm) Solder Lugs Axial, Box R (0.01%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%)	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
Package / Case Axial, Box Failure Rate R (0.01%)	Height - Seated (Max)	0.625" (15.87mm)
Failure Rate R (0.01%)	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	R (0.01%)
		Report errors?

RER75F7871RC02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER75F7871RC02 Payment Methods



















RER75F7871RC02 Shipping Methods













If you have any question about RER75F7871RC02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com