

## RER75F9530RCSL

### **RER75F9530RCSL Information**

Heisener.com

Part Number RER75F9530RCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 953 OHM 1% 30W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER75F9530RCSL Specifications**

Manufacturer Part NumberRER75F9530RCSLManufacturerVishay DaleCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance953 OhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°C
Category  Resistors  Chassis Mount Resistors  Package  Axial, Box  Series  Military, MIL-PRF-39009, RER75  Resistance  953 Ohms  Tolerance  ±1%  Power (Watts)  30W  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C
Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER75  Resistance 953 Ohms  Tolerance ±1%  Power (Watts) 30W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance953 OhmsTolerance $\pm 1\%$ Power (Watts)30WCompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
SeriesMilitary, MIL-PRF-39009, RER75Resistance953 OhmsTolerance $\pm 1\%$ Power (Watts)30WCompositionWirewoundTemperature Coefficient $\pm 20$ ppm/°COperating Temperature $-55$ °C ~ $250$ °C
Resistance953 OhmsTolerance $\pm 1\%$ Power (Watts) $30W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Tolerance $\pm 1\%$ Power (Watts) $30W$ CompositionWirewoundTemperature Coefficient $\pm 20 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 250^{\circ}C$
Power (Watts) $30W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55 \text{°C} \sim 250 \text{°C}$
Temperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$
Features Military, Moisture Resistant
Coating, Housing Type Aluminum
Mounting Feature Flanges
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)
Height - Seated (Max) 0.625" (15.87mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate R (0.01%)
Report errors?

### **RER75F9530RCSL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **RER75F9530RCSL Payment Methods**



















### **RER75F9530RCSL Shipping Methods**













If you have any question about RER75F9530RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com