

RER75FR150RCSL

RER75FR150RCSL Information

Heisener.com

Part Number RER75FR150RCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 0.15 OHM 1% 30W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER75FR150RCSL Specifications

| Manufacturer Part Number RER75FR150RCSL Manufacturer Vishay Dale Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 150 mOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate Report errors? | | |
|---|--------------------------|---|
| Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 150 mOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Manufacturer Part Number | RER75FR150RCSL |
| Chassis Mount Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER75 Resistance 150 mOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate (0.01%) | Manufacturer | Vishay Dale |
| PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER75Resistance150 mOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%) | Category | Resistors |
| SeriesMilitary, MIL-PRF-39009, RER75Resistance150 mOhmsTolerance±1%Power (Watts)30WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.625" (15.87mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%) | | Chassis Mount Resistors |
| Resistance 150 mOhms Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Package | Axial, Box |
| Tolerance ±1% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Series | Military, MIL-PRF-39009, RER75 |
| Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%) | Resistance | 150 mOhms |
| Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R(0.01%) | Tolerance | ±1% |
| Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Power (Watts) | 30W |
| Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Composition | Wirewound |
| Features Military, Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Temperature Coefficient | ±100ppm/°C |
| Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Operating Temperature | -55°C ~ 250°C |
| Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate R (0.01%) | Features | Military, Moisture Resistant |
| Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.625" (15.87mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate R (0.01%) | Coating, Housing Type | Aluminum |
| Height - Seated (Max) Lead Style Package / Case Failure Rate 0.625" (15.87mm) Solder Lugs Axial, Box R (0.01%) | Mounting Feature | Flanges |
| Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateR (0.01%) | Size / Dimension | 1.968" L x 1.140" W (49.99mm x 28.96mm) |
| Package / Case Axial, Box Failure Rate R (0.01%) | Height - Seated (Max) | 0.625" (15.87mm) |
| Failure Rate R (0.01%) | Lead Style | Solder Lugs |
| | Package / Case | Axial, Box |
| Report errors? | Failure Rate | R (0.01%) |
| | | Report errors? |

RER75FR150RCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER75FR150RCSL Payment Methods



















RER75FR150RCSL Shipping Methods













If you have any question about RER75FR150RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com