



RGEF300K-2 Information

Heisener.com

Part Number RGEF300K-2

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description POLYSWITCH PTC RESET 3A HLD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RGEF300K-2 Specifications

Manufacturer Part Number RGEF300K-2 Manufacturer Littelfuse Inc. Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series PolySwitch?, RGEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series PolySwitch?, RGEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature Circuit Protection PTC Resettable Fuses Radial, Disc PolySwitch?, RGEF PolySwitch? PolySwitch?, RGEF PolySwitch? PolySwitch?, RGEF PolySwitch? PolySwi
Package Radial, Disc Series PolySwitch?, RGEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ)40°C ~ 85°C
PackageRadial, DiscSeriesPolySwitch?, RGEFTypePolymericVoltage - Max16VCurrent - Max100ACurrent - Hold (Ih) (Max)3ACurrent - Trip (It)5.1ATime to Trip1sResistance - Initial (Ri) (Min)38 mOhmsResistance - Post Trip (R1) (Max)97.5 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°C
Series PolySwitch?, RGEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C
Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C
Voltage - Max Current - Max 100A Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature 16V 100A 3A 3A 5.1A 1s 7.5 mOhms 97.5 mOhms - 40°C ~ 85°C
Current - Max Current - Hold (Ih) (Max) 3A Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C
Current - Hold (Ih) (Max) Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature 3A 5.1A 1s 7.5 mOhms 97.5 mOhms -40°C ~ 85°C
Current - Trip (It) 5.1A Time to Trip 1s Resistance - Initial (Ri) (Min) 38 mOhms Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) - 40°C ~ 85°C
Time to Trip Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature 1s 38 mOhms 97.5 mOhms - 40°C ~ 85°C
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature 38 mOhms 97.5 mOhms -40°C ~ 85°C
Resistance - Post Trip (R1) (Max) 97.5 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C
Resistance - 25° C (Typ) - -40° C ~ 85° C
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ratings -
Mounting Type Through Hole
Package / Case Radial, Disc
Size / Dimension 0.260" L x 0.098" W (6.60mm x 2.50mm)
Height - Seated (Max) 0.535" (13.60mm)
Thickness (Max)
Lead Spacing 0.199" (5.05mm)
Report errors?

RGEF300K-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RGEF300K-2 Payment Methods



















RGEF300K-2 Shipping Methods













If you have any question about RGEF300K-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com