



RHEF550 Information



Part Number RHEF550

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description POLYSWITCH PTC RESET 5.5A HOLD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RHEF550 Specifications

| Manufacturer Part Number RHEF550 Manufacturer Littelfuse Inc. Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series PolySwitch?, RHEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (lh) (Max) 5.5A Current - Trip (lt) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) 0.100" (5.05mm) | KIIII 330 Specifications | |
|--|-----------------------------------|--|
| Category Circuit Protection Package Radial, Disc Series PolySwitch?, RHEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (lh) (Max) 5.5A Current - Trip (lt) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Manufacturer Part Number | RHEF550 |
| Package Radial, Disc Series PolySwitch?, RHEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Manufacturer | Littelfuse Inc. |
| Package Radial, Disc Series PolySwitch?, RHEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Category | Circuit Protection |
| Series PolySwitch?, RHEF Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | | PTC Resettable Fuses |
| Type Polymeric Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Package | Radial, Disc |
| Voltage - Max 16V Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Series | PolySwitch?, RHEF |
| Current - Max 100A Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Туре | Polymeric |
| Current - Hold (Ih) (Max) 5.5A Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Voltage - Max | 16V |
| Current - Trip (It) 10A Time to Trip 6s Resistance - Initial (Ri) (Min) 15 mOhms Resistance - Post Trip (R1) (Max) 37 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Current - Max | 100A |
| Time to Trip Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) Thickness (Max) - | Current - Hold (Ih) (Max) | 5.5A |
| Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) - 15 mOhms 17 mOhms 18 m | Current - Trip (It) | 10A |
| Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 7. Thickness (Max) - | Time to Trip | 6s |
| Resistance - 25°C (Typ) Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension O.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) Thickness (Max) - | Resistance - Initial (Ri) (Min) | 15 mOhms |
| Operating Temperature -40°C ~ 125°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 7 Thickness (Max) - | Resistance - Post Trip (R1) (Max) | 37 mOhms |
| Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Resistance - 25°C (Typ) | - |
| Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) | Operating Temperature | -40°C ~ 125°C |
| Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) | Ratings | - |
| Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.740" (18.90mm) Thickness (Max) - | Mounting Type | Through Hole |
| Height - Seated (Max) 7. Thickness (Max) 0.740" (18.90mm) - | Package / Case | Radial, Disc |
| Thickness (Max) | Size / Dimension | 0.441" Dia x 0.118" W (11.20mm x 3.00mm) |
| | Height - Seated (Max) | 0.740" (18.90mm) |
| Load Spacing 0.100" (5.05mm) | Thickness (Max) | - |
| Lead Spacing 0.199 (3.0311111) | Lead Spacing | 0.199" (5.05mm) |
| Report errors? | | Report errors? |

RHEF550 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RHEF550 Payment Methods


































If you have any question about RHEF550, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com