

# **RJS 100-R SHORT**

#### **RJS 100-R SHORT Information**

Heisener.com

Part Number RJS 100-R SHORT

Manufacturer Bel Fuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE BRD MNT 100MA 600VAC RADIAL

Package Radial Bend Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RJS 100-R SHORT Specifications**

Manufacturer Part Number  Manufacturer  Bel Fuse Inc.  Circuit Protection  Electrical, Specialty Fuses  Package  Radial Bend Cylinder  Series  RJS  Fuse Type  Board Mount  Current Rating  100mA  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Response Time  Roll Time Applications  Telecom  - CE, CSA, cURus  Operating Temperature  Breaking Capacity @ Rated Voltage  Radial Bend Cylinder  Size / Dimension  Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Radial Bend Cylinder  Series  RJS  Fuse Type  Board Mount  Current Rating  100mA  Voltage Rating - AC  600V  Voltage Rating - DC  Response Time  Slow  Applications  Telecom  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Radial Bend Cylinder  Radial Bend Cylinder  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Radial Bend Cylinder  Electrical, Specialty Fuses  Radial Bend Cylinder  Electrical, Specialty Fuses  Radial Bend Cylinder  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Radial Bend Cylinder  Size / Dimension	Manufacturer Part Number	RJS 100-R SHORT
PackageRadial Bend CylinderSeriesRJSFuse TypeBoard MountCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, cURusOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Manufacturer	Bel Fuse Inc.
PackageRadial Bend CylinderSeriesRJSFuse TypeBoard MountCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, cURusOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Category	Circuit Protection
SeriesRJSFuse TypeBoard MountCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, cURusOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.181" Dia x 0.760" L (4.60mm x 19.30mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100mA  Voltage Rating - AC 600V  Voltage Rating - DC - Response Time Slow Applications Telecom Features - Class - Approvals CE, CSA, cURus Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension Board Mount 100mA  600V	Package	Radial Bend Cylinder
Current Rating Voltage Rating - AC  Voltage Rating - DC  Response Time Slow Applications Telecom  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension  100mA 600V  - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V - 600V	Series	RJS
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Telecom  Features  - Class  - Approvals  CE, CSA, cURus  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Size / Dimension  600V  -	Fuse Type	Board Mount
Voltage Rating - DC  Response Time  Slow  Applications  Telecom  Features  - Class  - Approvals  CE, CSA, cURus  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Size / Dimension  - Slow  Telecom  - CE, CSA, cURUS  - CE, CSA	Current Rating	100mA
Response Time  Applications  Telecom  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Size / Dimension  Slow  Telecom  - CE, CSA, cURus  - CE, CSA, cURus  - 55°C ~ 125°C  100A  Through Hole  Radial Bend Cylinder  0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Voltage Rating - AC	600V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension  Telecom  Though  Though  Though  Though  Through Hole  Radial Bend Cylinder  O.181" Dia x 0.760" L (4.60mm x 19.30mm)	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 100A Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Response Time	Slow
Class - CE, CSA, cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 100A Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Applications	Telecom
Approvals  CE, CSA, cURus  Operating Temperature  -55°C ~ 125°C  Breaking Capacity @ Rated Voltage  100A  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Size / Dimension  O.181" Dia x 0.760" L (4.60mm x 19.30mm)	Features	-
Operating Temperature  -55°C ~ 125°C  Breaking Capacity @ Rated Voltage  100A  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Size / Dimension  0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Class	-
Breaking Capacity @ Rated Voltage 100A  Mounting Type Through Hole  Package / Case Radial Bend Cylinder  Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Approvals	CE, CSA, cURus
Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Operating Temperature	-55°C ~ 125°C
Package / Case Radial Bend Cylinder Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Breaking Capacity @ Rated Voltage	100A
Size / Dimension 0.181" Dia x 0.760" L (4.60mm x 19.30mm)	Mounting Type	Through Hole
	Package / Case	Radial Bend Cylinder
Report errors?	Size / Dimension	0.181" Dia x 0.760" L (4.60mm x 19.30mm)
		Report errors?

#### **RJS 100-R SHORT Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RJS 100-R SHORT Payment Methods**



















## **RJS 100-R SHORT Shipping Methods**













If you have any question about RJS 100-R SHORT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com