

### **RJS125 Information**



For Reference Only

Part Number RJS125 Manufacturer Ohmite

**Category** Potentiometers, Variable Resistors Rotary Potentiometers, Rheostats

**Description** POT 125 OHM 50W WIREWOUND LINEAR

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RJS125 Specifications**

Manufacturer Part Number         RJS125           Manufacturer         Ohmite           Category         Potentiometers, Variable Resistors           Rotary Potentiometers, Rheostats         Resistance           Package         -           Series         J           Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	•	
Category         Potentiometers, Variable Resistors           Package         -           Series         J           Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	Manufacturer Part Number	RJS125
Package         -           Series         J           Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	Manufacturer	Ohmite
Package         -           Series         J           Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	Category	Potentiometers, Variable Resistors
Series         J           Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount		Rotary Potentiometers, Rheostats
Taper         Linear           Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	Package	-
Resistance (Ohms)         125           Tolerance         ±10%           Number of Gangs         1           Built in Switch         None           Power (Watts)         50W           Temperature Coefficient         -           Number of Turns         1           Rotation         300°           Adjustment Type         User Defined           Resistive Material         Wirewound           Termination Style         Solder Lug           Actuator Type         Flatted           Actuator Length         0.875" (22.23mm)           Actuator Diameter         0.250" (6.35mm)           Bushing Thread         3/8-32           Mounting Type         Panel Mount	Series	J
Tolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)50WTemperature Coefficient-Number of Turns1Rotation300°Adjustment TypeUser DefinedResistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length0.875" (22.23mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Taper	Linear
Number of Gangs1Built in SwitchNonePower (Watts)50WTemperature Coefficient-Number of Turns1Rotation300°Adjustment TypeUser DefinedResistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length0.875" (22.23mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Resistance (Ohms)	125
Built in SwitchNonePower (Watts)50WTemperature Coefficient-Number of Turns1Rotation300°Adjustment TypeUser DefinedResistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length0.875" (22.23mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Tolerance	±10%
Power (Watts) 50W Temperature Coefficient - Number of Turns 1 Rotation 300° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 0.875" (22.23mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Number of Gangs	1
Temperature Coefficient  Number of Turns  1 Rotation 300° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length O.875" (22.23mm) Actuator Diameter O.250" (6.35mm) Bushing Thread Mounting Type Panel Mount	Built in Switch	None
Number of Turns  Rotation  300°  Adjustment Type  User Defined  Wirewound  Termination Style  Actuator Type  Flatted  Actuator Length  Actuator Diameter  Bushing Thread  Mounting Type  1  1  1  1  1  1  1  1  1  1  1  1  1	Power (Watts)	50W
Rotation 300° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 0.875" (22.23mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Temperature Coefficient	-
Adjustment Type Resistive Material Wirewound Termination Style Actuator Type Flatted Actuator Length O.875" (22.23mm) Actuator Diameter Bushing Thread Mounting Type User Defined Virewound O.30der Lug Solder Lug Flatted O.875" (22.23mm) O.250" (6.35mm) Panel Mount	Number of Turns	1
Resistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length0.875" (22.23mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Rotation	300°
Termination Style  Actuator Type Flatted  Actuator Length O.875" (22.23mm)  Actuator Diameter O.250" (6.35mm)  Bushing Thread Mounting Type Panel Mount	Adjustment Type	User Defined
Actuator Type Flatted  Actuator Length 0.875" (22.23mm)  Actuator Diameter 0.250" (6.35mm)  Bushing Thread 3/8-32  Mounting Type Panel Mount	Resistive Material	Wirewound
Actuator Length 0.875" (22.23mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Termination Style	Solder Lug
Actuator Diameter 0.250" (6.35mm)  Bushing Thread 3/8-32  Mounting Type Panel Mount	Actuator Type	Flatted
Bushing Thread 3/8-32 Mounting Type Panel Mount	Actuator Length	0.875" (22.23mm)
Mounting Type Panel Mount	Actuator Diameter	0.250" (6.35mm)
	Bushing Thread	3/8-32
D0	Mounting Type	Panel Mount
Report errors?		Report errors?

### **RJS125 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RJS125 Payment Methods**





















## **RJS125 Shipping Methods**













If you have any question about RJS125, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com