



### **RL07S221GRE6 Information**

Heisener.com

Part NumberRL07S221GRE6ManufacturerVishay DaleCategoryResistors

**Through Hole Resistors** 

**Description** RES 220 OHM 1/4W 2% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **RL07S221GRE6 Specifications**

Manufacturer Part NumberRL07S221GRE6ManufacturerVishay DaleCategoryResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance220 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Heigh - Seated (Max)-Number of Terminations2	•	
Category Resistors Through Hole Resistors  Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 220 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200pm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Manufacturer Part Number	RL07S221GRE6
Through Hole Resistors  Package Axial  Series Military, MIL-PRF-22684/01, RL07  Resistance 220 Ohms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations 2	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance220 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2	Category	Resistors
Series Military, MIL-PRF-22684/01, RL07  Resistance 220 Ohms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations 2		Through Hole Resistors
Resistance 220 Ohms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations 2	Package	Axial
Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max) -  Number of Terminations 2	Series	Military, MIL-PRF-22684/01, RL07
Power (Watts)  Composition  Metal Film  Features  Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case  Axial  Supplier Device Package  Axial  Size / Dimension  0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations  2	Resistance	220 Ohms
Composition  Metal Film  Features  Flame Retardant Coating, Military, Moisture Resistant, Safety  ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case  Axial  Supplier Device Package  Axial  Size / Dimension  0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations  2	Tolerance	±2%
Features  Flame Retardant Coating, Military, Moisture Resistant, Safety  ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case  Axial  Supplier Device Package  Axial  Size / Dimension  0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations  2	Power (Watts)	0.25W, 1/4W
Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max) -  Number of Terminations 2	Composition	Metal Film
Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations 2	Features	Flame Retardant Coating, Military, Moisture Resistant, Safety
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Temperature Coefficient	±200ppm/°C
Supplier Device Package Axial  Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max)  Number of Terminations 2	Operating Temperature	-65°C ~ 175°C
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)  Height - Seated (Max) -  Number of Terminations 2	Package / Case	Axial
Height - Seated (Max) - Number of Terminations 2	Supplier Device Package	Axial
Number of Terminations 2	Size / Dimension	0.090" Dia x 0.240" L (2.29mm x 6.10mm)
	Height - Seated (Max)	-
	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

### **RL07S221GRE6 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **RL07S221GRE6 Payment Methods**



















## **RL07S221GRE6 Shipping Methods**













If you have any question about RL07S221GRE6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com