



### **RL07S472GRE6 Information**

Heisener.com

Part NumberRL07S472GRE6ManufacturerVishay DaleCategoryResistors

Through Hole Resistors

**Description** RES 4.7K OHM 1/4W 2% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RL07S472GRE6 Specifications**

Manufacturer Part NumberRL07S472GRE6ManufacturerVishay DaleCategoryResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance4.7 kOhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)
Category Resistors Through Hole Resistors  Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 4.7 kOhms  Tolerance ±2% Power (Watts) 0.25W, 1/4W  Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial
Through Hole Resistors  Package Axial  Series Military, MIL-PRF-22684/01, RL07  Resistance 4.7 kOhms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial
Package Axial  Series Military, MIL-PRF-22684/01, RL07  Resistance 4.7 kOhms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial
Series Military, MIL-PRF-22684/01, RL07  Resistance 4.7 kOhms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial
Resistance 4.7 kOhms  Tolerance ±2%  Power (Watts) 0.25W, 1/4W  Composition Metal Film  Features Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient ±200ppm/°C  Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial
Tolerance $\pm 2\%$ Power (Watts) $0.25W$ , $1/4W$ CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient $\pm 200 \text{ppm/°C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$ Package / CaseAxialSupplier Device PackageAxial
Power (Watts)  Composition  Metal Film  Features  Flame Retardant Coating, Military, Moisture Resistant, Safety  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case  Axial  Supplier Device Package  Axial
CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient $\pm 200 \text{ppm/°C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$ Package / CaseAxialSupplier Device PackageAxial
Features  Flame Retardant Coating, Military, Moisture Resistant, Safety  ±200ppm/°C  Operating Temperature  -65°C ~ 175°C  Package / Case  Axial  Supplier Device Package  Axial
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$ Package / Case Axial  Supplier Device Package Axial
Operating Temperature -65°C ~ 175°C  Package / Case Axial  Supplier Device Package Axial
Package / Case Axial Supplier Device Package Axial
Supplier Device Package Axial
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)
` '
Height - Seated (Max)
Number of Terminations 2
Failure Rate -
Report errors?

#### **RL07S472GRE6 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **RL07S472GRE6 Payment Methods**



















# **RL07S472GRE6 Shipping Methods**













If you have any question about RL07S472GRE6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com