



RL07S512GBSL Information

Heisener.com

Part NumberRL07S512GBSLManufacturerVishay DaleCategoryResistors

Through Hole Resistors

Description RES 5.1K OHM 1/4W 2% AXIAL

Package Axial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL07S512GBSL Specifications

Manufacturer Part Number Manufacturer Vishay Dale Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 5.1 kOhms Tolerance +2% Power (Watts) Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension Device Package Axial Size / Dimension Double Activity Secret (Mary)	•	
Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 5.1 kOhms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension Resistors Military, MIL-PRF-22684/01, RL07 Axial Size / Dimension O.25W, 1/4W Axial O.25W, 1/4W O.25	Manufacturer Part Number	RL07S512GBSL
Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 5.1 kOhms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance5.1 kOhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Category	Resistors
Series Military, MIL-PRF-22684/01, RL07 Resistance 5.1 kOhms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)		Through Hole Resistors
Resistance 5.1 kOhms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Package	Axial
Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Series	Military, MIL-PRF-22684/01, RL07
Power (Watts) Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Resistance	5.1 kOhms
Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension Metal Film £200pm/°C Axial £200ppm/°C Axial Axial Supplier Device Package Axial \$0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Tolerance	$\pm 2\%$
Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension O.090" Dia x 0.240" L (2.29mm x 6.10mm)	Power (Watts)	0.25W, 1/4W
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$ Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090° Dia x 0.240° L $(2.29 \text{mm x } 6.10 \text{mm})$	Composition	Metal Film
Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Features	Flame Retardant Coating, Military, Moisture Resistant, Safety
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Temperature Coefficient	±200ppm/°C
Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Operating Temperature	-65°C ~ 175°C
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)	Package / Case	Axial
	Supplier Device Package	Axial
Height Social (May)	Size / Dimension	0.090" Dia x 0.240" L (2.29mm x 6.10mm)
rieight - Seated (Max)	Height - Seated (Max)	-
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

RL07S512GBSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL07S512GBSL Payment Methods





















RL07S512GBSL Shipping Methods













If you have any question about RL07S512GBSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com