



RL07S680GBSL Information

Heisener.com

Part NumberRL07S680GBSLManufacturerVishay DaleCategoryResistors

Through Hole Resistors

Description RES 68 OHM 1/4W 2% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL07S680GBSL Specifications

Manufacturer Part NumberRL07S680GBSLManufacturerVishay DaleCategoryResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance68 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2	•	
Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 68 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200pm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Manufacturer Part Number	RL07S680GBSL
Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 68 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance68 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2	Category	Resistors
Series Military, MIL-PRF-22684/01, RL07 Resistance 68 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2		Through Hole Resistors
Resistance 68 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Package	Axial
Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Series	Military, MIL-PRF-22684/01, RL07
Power (Watts) Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Resistance	68 Ohms
Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Tolerance	±2%
Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Power (Watts)	0.25W, 1/4W
Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Composition	Metal Film
Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Features	Flame Retardant Coating, Military, Moisture Resistant, Safety
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Temperature Coefficient	±200ppm/°C
Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Operating Temperature	-65°C ~ 175°C
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Package / Case	Axial
Height - Seated (Max) - Number of Terminations 2	Supplier Device Package	Axial
Number of Terminations 2	Size / Dimension	0.090" Dia x 0.240" L (2.29mm x 6.10mm)
	Height - Seated (Max)	-
	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

RL07S680GBSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL07S680GBSL Payment Methods



















RL07S680GBSL Shipping Methods













If you have any question about RL07S680GBSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com