



RL07S911GRE6 Information

Heisener.com

For Reference Only

Part NumberRL07S911GRE6ManufacturerVishay DaleCategoryResistors

Through Hole Resistors

Description RES 910 OHM 1/4W 2% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL07S911GRE6 Specifications

Manufacturer Part NumberRL07S911GRE6ManufacturerVishay DaleCategoryResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance910 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	•	
Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 910 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200pm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Manufacturer Part Number	RL07S911GRE6
Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/01, RL07 Resistance 910 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-22684/01, RL07Resistance910 OhmsTolerance±2%Power (Watts)0.25W, 1/4WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2	Category	Resistors
Series Military, MIL-PRF-22684/01, RL07 Resistance 910 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2		Through Hole Resistors
Resistance 910 Ohms Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Package	Axial
Tolerance ±2% Power (Watts) 0.25W, 1/4W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Series	Military, MIL-PRF-22684/01, RL07
Power (Watts) Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Resistance	910 Ohms
Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Tolerance	±2%
Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Power (Watts)	0.25W, 1/4W
Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Composition	Metal Film
Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Features	Flame Retardant Coating, Military, Moisture Resistant, Safety
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Temperature Coefficient	±200ppm/°C
Supplier Device Package Axial Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) Number of Terminations 2	Operating Temperature	-65°C ~ 175°C
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm) Height - Seated (Max) - Number of Terminations 2	Package / Case	Axial
Height - Seated (Max) - Number of Terminations 2	Supplier Device Package	Axial
Number of Terminations 2	Size / Dimension	0.090" Dia x 0.240" L (2.29mm x 6.10mm)
	Height - Seated (Max)	-
Failure Rate -	Number of Terminations	2
	Failure Rate	-
Report errors?		Report errors?

RL07S911GRE6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL07S911GRE6 Payment Methods



















RL07S911GRE6 Shipping Methods













If you have any question about RL07S911GRE6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com